

FIBER TERMINATION BOX · METAL TERMINATION BOX

METAL TERMINATION BOX



BRIEF

Fiber Optic Distribution Box is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.

FEATURES

Material: Galvanized steel. Clamping for feeder cable, fiber splicing, fixation, storage, distribution, etc. all in one. The splicing tray can be removed to facilitate the splicing of large-core optical cables. Box can be installed by the way of wall-mounted, suitable for indoor.

SPECIFICATIONS

Assembly	Empty	Cable entry size	≤28mm
Product Color	Light grey	Relative humidity	≤85% (+30°C)
Fiber Count	48 core	Installation Type	Wall-mounted
Protection Class	IP 53	Atmospheric pressure	70KPa~106Kpa
Adaptor	Max 24 pcs LC Duplex	Box Material	Galvanized Steel
Working Temperature	-40~+60°C		

ORDERING INFORMATION

PRODUCT REFERENCE	DESCRIPTION
SW1318 4003	Metal Termination Box

Metal Termination Box.

Manufactured by Elsewedy Telecom Cables A.R.E., 10th of Ramadan City, Industrial Zone (A3), Egypt.